

**Order Code: XCNC2X1M3MS**

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



**Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [11W/13W/16W/18W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

**Construction**

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

**Installation Notes**

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation



**Technical Data**

**General**

Luminaire Wattage (W)	11W/13W/16W/18W
Weight (kg)	1.53
Operating Temperature (ta °C)	5° to 25°

**Light Output**

Lumens (lm)	1600 to 2700
Efficacy (lm/W)	151

**LED**

CRI	80
Macadam Ellipses	6.7

**Driver**

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	42.7 to 45.6Vdc

**Emergency**

Emergency Lumen Operating	318
Emergency Wattage (W)	2

**Electrical**

Rated Input Current (A)	0.06 to 0.09
Power Factor (pf)	0.86 to 0.93
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	175
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

**Order Code: XCNC2X1M3MS**

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

Dimensions

A (mm)	675
B (mm)	80
C (mm)	95
Fix	400

Line Drawing

