

**Order Code:** XCNC2X1MS  
600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [11 to 18] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular emergency and sensor pack for quick and easy conversion

Installation Notes

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	11 to 18	Rated Input Current (A)	0.06 to 0.09
Weight (kg)	0.93	Power Factor (pf)	0.86 to 0.93
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	175
Lumens (lm)	1600 to 2700	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	151	Terminal Type	3 pole piano key
LED			
CRI	80		
Macadam Elipses	6.7		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	42.7 to 45.6Vdc		

**Order Code:** XCNC2X1MS  
600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

Dimensions

A (mm)	675
B (mm)	80
C (mm)	95
Fix	400

Line Drawing

