xcite LED Lighting

Data Sheet



Order Code: XCNC2X1MS

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [11W/13W/16W/18W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular microwave sensor for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available



Conduit and BESA fixing points for end or rear cable entry Loop in/out push-fit terminal block for quick installation

















Technical Data

General		Electrical	
Luminaire Wattage (W)	11W/13W/16W/18W	Rated Input Current (A)	0.06 to 0.09
Weight (kg)	0.93	Power Factor (pf)	0.86 to 0.93
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output	Inrush Current Peak (A)	175	
Light Output Lumens (Im)	1600 to 2700	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	151	Terminal Type	3 pole piano key
LED			
CRI	80		
Macadam Elipses	6.7		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	42.7 to 45.6Vdc		



xcite LED Lighting

Data Sheet



Order Code: XCNC2X1MS

600mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

Dimensions

A (mm)	675
B (mm)	80
C (mm)	95
Fix	400

Line Drawing



