# xcite LED Lighting

### **Data Sheet**



Order Code: XCNC5X1M3

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency



#### **Features**

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [29W/36W/43W/50W] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

#### Construction

- · Grey polycarbonate body
- Weatherproof IP65 construction
- Modular microwave sensor for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

#### **Installation Notes**

Conduit and BESA fixing points for end or rear cable entry Loop in/out push-fit terminal block for quick installation

















#### **Technical Data**

General		Electrical	
Luminaire Wattage (W)	29W/36W/43W/50W	Rated Input Current (A)	0.14 to 0.24
Weight (kg)	2.45	Power Factor (pf)	0.89 to 0.95
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
l inht O		Inrush Current Peak (A)	200
Light O Lumens (Im)	4700 to 7900	Conductor Size (mm)	0.5 to 2.5
Ffficacy (Im/W)	162	Terminal Type	4 nole niano key
LEC	)		
CRI	80		
Macadam Elipses	6.5		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	124 to 134.1Vdc		
Emerge	ency		
Emergency Lumen Operating	327		
Emergency Wattage (W)	2		



## xcite LED Lighting

### **Data Sheet**



Order Code: XCNC5X1M3

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency

#### **Dimensions**

A (mm)	1570
B (mm)	80
C (mm)	95
Fix	600

#### Line Drawing



