

Order Code: XCNC5X1M3MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Wattage [29 to 52] adjustable via 2-way dip switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular emergency and sensor pack for quick and easy conversion

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General

Luminaire Wattage (W)	29 to 52
Weight (kg)	2.55
Operating Temperature (ta °C)	5° to 25°

Light Output

Lumens (lm)	4700 to 7900
Efficacy (lm/W)	162

LED

CRI	80
Macadam Elipses	6.5

Driver

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	124 to 134.1Vdc

Emergency

Emergency Lumen Operating	327
Emergency Wattage (W)	2

Electrical

Rated Input Current (A)	0.14 to 0.24
Power Factor (pf)	0.89 to 0.95
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	200
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

**Order Code: XCNC5X1M3MS**

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Emergency - Microwave sensor

Dimensions

A (mm)	1570
B (mm)	80
C (mm)	95
Fix	600

Line Drawing

