

### Order Code: XCNC5X1MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor



#### Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Wattage adjustable via 2-way dip switch [29W/36W/43W/50]
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

#### Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [emergency pack](#) and [microwave sensor](#)'s available for quick and easy conversion of a standard fitting
- Pre-assembled emergency and sensor luminaires available

#### Installation Notes

Conduit and BESA fixing points for end or rear cable entry  
Loop in/out push-fit terminal block for quick installation



#### Technical Data

##### General

Luminaire Wattage (W)	29W/36W/43W/50
Weight (kg)	1.95
Operating Temperature (ta °C)	-20° to +25°

##### Light Output

Lumens (lm)	4700 - 7900
Efficacy (lm/W)	162

##### LED

CCT (K)	3000K/4000K/6000K
CRI	80
Macadam Elipses	6.5

##### Driver

Driver Current (mA)	200, 250, 300, 350
Forward Voltage (V)	124 to 134.1Vdc

##### Electrical

Rated Input Current (A)	0.14 to 0.24
Power Factor (pf)	0.89 to 0.95
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	45A
Surge Protection (kV)	1
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3 pole piano key

### Order Code: XCNC5X1MS

1500mm - CCT [3000K/4000K/6000K] + Wattage Selectable - Microwave sensor

#### Dimensions

A (mm)	1570
B (mm)	95
B (mm)	80
Fix	600

#### Line Drawing

