

Order Code: XCNC6X1

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable



Features

- Suitable for a range of commercial and industrial applications
- Available in 4 lengths [2ft, 4ft, 5ft, and 6ft]
- Modular EMG & Sensor option available
- CCT [3000K/4000K/6000K] adjustable via 3-way selector switch
- Position adjustable mounting clips
- Stainless steel retainer clips for diffuser with anti-tamper screw

Construction

- Grey polycarbonate body
- Weatherproof IP65 construction
- Modular [microwave sensor](#) for quick and easy conversion available
- Pre-assembled emergency and sensor luminaires available

Installation Notes

Conduit and BESA fixing points for end or rear cable entry
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	35W/44W/53W/62W	Rated Input Current (A)	0.17 to 0.29
Weight (kg)	2.21	Power Factor (pf)	0.92 to 0.96
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	200
Light Output		Conductor Size (mm)	0.5 to 2.5
Lumens (lm)	6000 to 10400	Terminal Type	3 pole piano key
Efficacy (lm/W)	171		
LED			
CRI	80		
Macadam Ellipses	8		
Driver			
Driver Current (mA)	200, 250, 300, 350		
Forward Voltage (V)	155 to 164Vdc		

Order Code: XCNC6X1

1800mm - CCT [3000K/4000K/6000K] + Wattage Selectable

Dimensions

A (mm)	1875
B (mm)	80
C (mm)	95
Fix	600

Line Drawing

