# xcite LED Lighting

## **Data Sheet**



Order Code: XCRL100DLPC

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



#### **Features**

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- · Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 120 lumens per watt efficacy

#### Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED













### Technical Data

General	
Luminaire Wattage (W)	100
Weight (kg)	5 20
Operating Temperature (ta °C)	
Light Output	
Lumens (Im)	12000
Efficacy (lm/W)	120
LED	
CCT (K)	6000
CRI	70
Macadam Elipses	3
Driver	
Driver Current (mA)	464
Forward Voltage (V)	42 9

Electrical	
Rated Input Current (A)	0.65
Power Factor (pf)	0.97
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	52.5
Surge Protection (kV)	6
Conductor Size (mm)	1
Terminal Type	Bare wire

# xcite LED Lighting

# Data Sheet



### Order Code: XCRL100DLPC

100W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

#### **Dimensions**

A (mm)	715
B (mm)	280
C (mm)	138

### Line Drawing





