xcite LED Lighting

Data Sheet



Order Code: XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



Features

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- · Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 112 lumens per watt efficacy

Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED













Technical Data

	1 0011111	oui L
General		
Luminaire Wattage (W)	60	Ra
Weight (kg)	2 46	Po
Operating Temperature (ta °C)		In
Light Output		In
Lumens (lm)	6700	Sı
Efficacy (lm/W)	112	C
LED		Te
CCT (K)	6000	
CRI		
Macadam Elipses	3	
Driver		
Driver Current (mA)	270	
Forward Voltage (V)		

Electrical		
Rated Input Current (A)	0.4	
Power Factor (pf)	0.94	
Input Voltage Range (VAC)	120-240	
Inrush Current Peak (A)	33.2	
Surge Protection (kV)	4	
Conductor Size (mm)	1	
Terminal Type	Bare wire	



xcite LED Lighting

Data Sheet



Order Code: XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

Dimensions

A (mm)	500
B (mm)	212
C (mm)	118

Line Drawing





