# xcite LED Lighting
## Data Sheet

**Order Code:** XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K



### Features

- Ideal for replacement of SON fixtures or Metal Halide fixtures
- Available in 3 different outputs
- Photocell option available
- Available in 2 sizes
- Mounted via side-entry 48mm [30W/60W] or 60mm dia. spigot
- High quality toughened safety glass
- Up to 112 lumens per watt efficacy

### Construction

- Aluminium body finished in grey [RAL 7037]
- Supplied as standard with daylight [6000K] LED

6000K | 50,000 HOURS | 3YRS WARRANTY | IP65 | IK08

## Technical Data

### General

| | |
|---|---|
| Luminaire Wattage (W) | 60 |
| Weight (kg) | 2.46 |
| Operating Temperature (ta °C) | -20 to 25 |

### Light Output

| | |
|---|---|
| Lumens (lm) | 6700 |
| Efficacy (lm/W) | 112 |

### LED

| | |
|---|---|
| CCT (K) | 6000 |
| CRI | 70 |
| Macadam Elipses | 3 |

### Driver

| | |
|---|---|
| Driver Current (mA) | 270 |
| Forward Voltage (V) | 39.9 |

### Electrical

| | |
|---|---|
| Rated Input Current (A) | 0.4 |
| Power Factor (pf) | 0.94 |
| Input Voltage Range (VAC) | 120-240 |
| Inrush Current Peak (A) | 33.2 |
| Surge Protection (kV) | 4 |
| Conductor Size (mm) | 1 |
| Terminal Type | Bare wire |

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

# xcite LED Lighting

## Data Sheet

**Order Code:** XCRL60DLPC

60W - Outdoor Road Lantern - IP65 - Photocell Sensor - 6000K

### Dimensions

| | |
|---|---|
| Length (mm) | 500 |
| Width (mm) | 212 |
| Depth (mm) | 118 |

### Line Drawing




Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk