

Order Code: XCRLX1
3000K-5000K + Wattage Selectable



Features

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [110 to 135] adjustable via selector switch
- Up to 141 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [up to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	110 to 135	Rated Input Current (A)	0.49 to 0.61
Weight (kg)	3.58	Power Factor (pf)	0.95 to 0.97
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	300
Lumens (lm)	15800 - 18300	Surge Protection (kV)	1KV
Efficacy (lm/W)	141	Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	4 pole piano key
CRI	80		
Macadam Elipses	1.8 to 4.4		
Driver			
Driver Current (mA)	2900		
Forward Voltage (V)	43.7 to 46.3		

Order Code: XCRL LX1  
3000K-5000K + Wattage Selectable

Dimensions

A (mm)	555
B (mm)	210
C (mm)	90

Line Drawing

