xcite LED Lighting

Data Sheet

0.49 to 0.61 0.95 to 0.97 220 to 240

> 300 1KV

0.5 to 2.5 4 pole piano key

Order Code: XCRLLX1PC

3000K-5000K + Wattage Selectable + Photocell



Features

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [110W/120W/135W] adjustable via selector switch
- Up to 141 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [up to 60mm]

Installation Notes

Wired via screwless connector inside main body Loop in/out push-fit terminal block for quick installation



















Technical Data

Teermon Bata				
Ge	eneral			Electrical
Luminaire Wattage (W)		110W/120W/135W	Rated Input Current (A)	
Weight (kg)		3.72	Power Factor (pf)	
Operating Temperature (ta °C)		0° to 25°	Input Voltage Range (VAC)	
Light Out	t Output		Inrush Current Peak (A)	
Lumens (Im)	Cutput	15800 - 18300	Surge Protection (kV)	
Efficacy (lm/W)		141	Conductor Size (mm)	
			Terminal Type	
L	_ED			
CRI		80		
Macadam Elipses		1.8 to 4.4		
D	river			
Driver Current (mA)		2900		
Forward Voltage (V)		43.7 to 46.3		

xcite LED Lighting

Data Sheet



Order Code: XCRLLX1PC

3000K-5000K + Wattage Selectable + Photocell

Dimensions

A (mm)	555
B (mm)	210
C (mm)	158

Line Drawing



