

Order Code: XCRLSX1
3000K-5000K + Wattage Selectable



Features

- CCT [3000K/4000K/5000K] adjustable via 3-way selector switch
- Wattage [40 to 60] adjustable via selector switch
- Up to 149 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [up to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General		Electrical	
Luminaire Wattage (W)	40 to 60	Rated Input Current (A)	0.19 to 0.27
Weight (kg)	2.55	Power Factor (pf)	0.95 to 0.97
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
Light Output		Inrush Current Peak (A)	60
Lumens (lm)	6000 - 8700	Surge Protection (kV)	1KV
Efficacy (lm/W)	149	Conductor Size (mm)	0.5 to 2.5
LED		Terminal Type	4 pole piano key
CRI	80		
Macadam Elipses	2.1 to 4.4		
Driver			
Driver Current (mA)	1090		
Forward Voltage (V)	43 to 50		

Order Code: XCRLSX1
3000K-5000K + Wattage Selectable

Dimensions

A (mm)	480
B (mm)	160
C (mm)	90

Line Drawing

