

Order Code: XCRLSX1PC

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell



Features

- CCT selectable via selector switch [3000K/4000K/5000K]
- Wattage selectable via selector switch [40W/50W/60W]
- Up to 149 lumens per watt efficacy

Construction

- Clear polycarbonate diffuser
- Aluminium body finished in grey [RAL 9007]
- Adjustable bracket for side entry or post-top mounting [42.6mm to 60mm]

Installation Notes

Wired via screwless connector inside main body
Loop in/out push-fit terminal block for quick installation



Technical Data

General

Luminaire Wattage (W)	40W/50W/60W
Weight (kg)	2.68
Operating Temperature (ta °C)	0° to 25°

Light Output

Lumens (lm)	6000 to 8700
Efficacy (lm/W)	149

LED

CCT (K)	3000K/4000K/5000K
CRI	80
Macadam Elipses	2.1 to 4.4

Driver

Driver Current (mA)	1090
Forward Voltage (V)	43 to 50

Electrical

Rated Input Current (A)	0.19 to 0.27
Power Factor (pf)	0.95 to 0.97
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	60
Surge Protection (kV)	1KV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

Order Code: XCRLSX1PC

X1 Road Lantern - CCT [3000K/4000K/5000K] + Wattage Selectable + Photocell

Dimensions

A (mm)	480
B (mm)	160
C (mm)	158

Line Drawing

