

Order Code: XCRP12650DL

50W - Recessed Edge-lit Panel - 1200mm x 600mm - 6000K



Features

- Ideal for retrofit of existing T5 or T8 fixtures
- Suitable for offices and schools
- 2 sizes available with 2.5mm light guide
- Compatible with [Panel Frame](#) and [Surface Panel Frame](#)
- 3 hours emergency maintained with compatible conversion box [Emergency Kit](#)
- Up to 100 lumens per watt efficacy

Construction

- Extruded aluminium frame
- High performance opal TP[b] diffuser
- Plug and play driver
- Emergency option available
- Supplied in warm white [3000K], neutral white [4000K], cool white [5000K] or daylight [6000K]

Technical Data

| General | | Electrical | |
|-------------------------------|---------|---------------------------|------------------|
| Luminaire Wattage (W) | 50 | Rated Input Current (A) | 0.22 |
| Weight (kg) | 5.30 | Power Factor (pf) | 0.9 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Inrush Current Peak (A) | 15.6 |
| Light Output | | Surge Protection (kV) | 2 |
| Lumens (lm) | 5000 | Conductor Size (mm) | 1.5 |
| Efficacy (lm/W) | 100 | Terminal Type | 2 pole grip wire |
| LED | | | |
| CCT (K) | 6000 | | |
| CRI | 80 | | |
| Macadam Elipses | 4 | | |

Order Code: XCRP12650DL

50W - Recessed Edge-lit Panel - 1200mm x 600mm - 6000K

Dimensions

| | |
|--------|------|
| A (mm) | 1195 |
| B (mm) | 595 |
| C (mm) | 10 |

Line Drawing

