

## Order Code: XCSBT631WWP

31W - 1800mm Batten - 3000K - PIR



## Features

- Ideal for replacement of linear fluorescent fixtures
- Suitable for general domestic and commercial use
- Available with PIR [VB1T] or PIR & Photocell [VB2T]
- Up to 124 lumens per watt efficacy

## Construction

- Steel body in white finish
- High quality opal diffuser to reduce glare
- Loop in/out mains connector
- Integral emergency option available
- Integral high quality driver and LED module
- Conduit and BESA fixing points for end or rear cable entry
- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]

## Technical Data

## General

Luminaire Wattage (W)	31
Weight (kg)	1.40
Operating Temperature (ta °C)	0 to 25

## Light Output

Lumens (lm)	3850
Efficacy (lm/W)	124

## LED

CCT (K)	3000
CRI	80
Macadam Ellipses	4

## Electrical

Rated Input Current (A)	0.14
Power Factor (pf)	0.9
Input Voltage Range (VAC)	220-240
Inrush Current Peak (A)	10
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole piano key

**Order Code: XCSBT631WWP**

31W - 1800mm Batten - 3000K - PIR

## Dimensions

A (mm)	1921
B (mm)	55
C (mm)	58
Fix	610

## Line Drawing

