xcite LED Lighting

Data Sheet



Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency



Features

- Suitable for open areas and escape routes
- Rear BESA fix and 3 additional rear fixing points
- Reduced maintenance and high performance
- Only 30mm depth for modern, slimline appearance
- Dual LED array for internal illumination and downward distribution
- Test switch fitted for easy testing
- EURO 1,2 & 4 running man legend also available [sold separately]

Construction

- Plastic body
- Hinged front lid for easy installation











Technical Data

General		Electrical	
Luminaire Wattage (W)	3.2	Rated Input Current (A)	0.029
Weight (kg)	0.65	Power Factor (pf)	0.46
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
LED CCT (K)		Conductor Size (mm)	1.5
	6500	Terminal Type	4 pole screw down
CRI	70		
Driver			
Driver Current (mA)	172		
Forward Voltage (V)	2.7		



xcite LED Lighting

Data Sheet



Order Code: XCSEBM3

3W - Emergency Slimline Exit Box with Arrow Up Legend - 3hrs Maintained Emergency

Dimensions

A (mm)	325
B (mm)	185
C (mm)	30

Line Drawing



