xcite LED Lighting

Data Sheet



Order Code: XCSEDLA1NM3CST

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test Corridor function



- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Supplied with LiFePO4 battery

Construction

- Very low energy consumption 1W
- Polycarbonate body
- Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance







Technical Data

General		Electrical	
Luminaire Wattage (W)	2	Rated Input Current (A)	0.02
Weight (kg)	0.30	Power Factor (pf)	0.19
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	220 to 240
155		Conductor Size (mm)	1.5
LED CRI	70	Terminal Type	3 nole screw down
Macadam Elipses	3.9		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	3.1		
Emergency			
Emergency Lumen Operating	130		
Emergency Wattage (W)	1		



xcite LED Lighting

Data Sheet



Order Code: XCSEDLA1NM3CST

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test Corridor function

Dimensions

A (mm)	170
B (mm)	120
C (mm)	45

Line Drawing



