xcite LED Lighting

Data Sheet



0.02

1.5

220 to 240

3 pole screw down

Order Code: XCSEDLA1NM3ST

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test

Features



- Suitable for open areas and escape routes
- 20mm conduit side and rear cable entries
- · Virtually service free emergency lighting
- Easy to install with simple connection wiring
- Supplied with LiFePO4 battery

Construction

- Very low energy consumption 1W
- Polycarbonate body
- · Operates in non-maintained mode
- Internal mains connection
- Integral auto self-test for reduced maintenance







Technical Data

General			Electrical
Luminaire Wattage (W)	2	Rated Input Current (A)	
Weight (kg)	0.30	Power Factor (pf)	
Operating Temperature (ta °C)	5° to 25°	Input Voltage Range (VAC)	
LED		Conductor Size (mm)	
LED CRI	70	Terminal Type	
Macadam Elipses	3.9		
Driver			
Driver Current (mA)	350		
Forward Voltage (V)	3.1		
Emergency			
Emergency Lumen Operating	130		
Emergency Wattage (W)	1		



xcite LED Lighting

Data Sheet



Order Code: XCSEDLA1NM3ST

XCITE EM SURFACE DOWNLIGHT ST XCSEDLA - 6500K - Fixed output - non-maintainted Emergency Self-test

Dimensions

A (mm)	170
B (mm)	120
C (mm)	45

Line Drawing



