

**Order Code: XCSF10WW**

10W - High Output Slim Floodlight - IP65 - 3000K - Black

**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 70 lumens per watt efficacy

**Construction**

- White or black body finish
- Breather gland for reducing condensation

**Technical Data****General**

Luminaire Wattage (W)	10
Weight (kg)	0.46
Operating Temperature (ta °C)	-20 to 25

**Light Output**

Lumens (lm)	700
Efficacy (lm/W)	70

**LED**

CCT (K)	3000
CRI	65
Macadam Ellipses	4

**Electrical**

Rated Input Current (A)	0.045
Power Factor (pf)	0.8
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	30
Surge Protection (kV)	0.5
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

**Order Code: XCSF10WW**

10W - High Output Slim Floodlight - IP65 - 3000K - Black

## Dimensions

A (mm)	153
B (mm)	110
C (mm)	40

## Line Drawing

