

**Order Code: XCSF150NW**

150W - High Output Slim Floodlight - IP65 - 4000K - Black



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 102 lumens per watt efficacy

**Construction**

- White or black body finish
- Breather gland for reducing condensation



**Technical Data**

| General                       |           | Electrical                |                   |
|-------------------------------|-----------|---------------------------|-------------------|
| Luminaire Wattage (W)         | 150       | Rated Input Current (A)   | 0.9               |
| Weight (kg)                   | 5.30      | Power Factor (pf)         | 0.9               |
| Operating Temperature (ta °C) | -20 to 25 | Input Voltage Range (VAC) | 100-305           |
|                               |           | Inrush Current Peak (A)   | 65                |
|                               |           | Surge Protection (kV)     | 1                 |
|                               |           | Conductor Size (mm)       | 1.5               |
|                               |           | Terminal Type             | 3 pole screw down |
| Light Output                  |           |                           |                   |
| Lumens (lm)                   | 15300     |                           |                   |
| Efficacy (lm/W)               | 102       |                           |                   |
| LED                           |           |                           |                   |
| CCT (K)                       | 4000      |                           |                   |
| CRI                           | 65        |                           |                   |
| Macadam Elipses               | 4         |                           |                   |

**Order Code:** XCSF150NW

150W - High Output Slim Floodlight - IP65 - 4000K - Black

Dimensions

|        |     |
|--------|-----|
| A (mm) | 485 |
| B (mm) | 325 |
| C (mm) | 110 |

Line Drawing

