xcite LED Lighting

Data Sheet



Order Code: XCSF150WW

150W - High Output Slim Floodlight - IP65 - 3000K - Black





- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 90 lumens per watt efficacy

Construction

- · White or black body finish
- Breather gland for reducing condensation













Technical Data

General		
Luminaire Wattage (W)	150	Rate
Weight (kg)	5.30	Pow
Operating Temperature (ta °C)		Inpu
Light Output		Inru
Lumens (lm)	13400	Sur
Efficacy (lm/W)	00	Con
		Terr
LED		
CCT (K)	3000	
CRI	65	
Macadam Elipses	4	

Electrical		
Rated Input Current (A)	0.9	
Power Factor (pf)	0.9	
Input Voltage Range (VAC)	100-305	
Inrush Current Peak (A)	65	
Surge Protection (kV)	1	
Conductor Size (mm)	1.5	
Terminal Type	3 pole screw down	

xcite LED Lighting

Data Sheet



Order Code: XCSF150WW

150W - High Output Slim Floodlight - IP65 - 3000K - Black

Dimensions

A (mm)	485
B (mm)	325
C (mm)	110

Line Drawing



