

Order Code: XCSF200WW
200W - High Output Slim Floodlight - IP65 - 3000K - Black



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 85 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation



Technical Data

General		Electrical	
Luminaire Wattage (W)	200	Rated Input Current (A)	1.2
Weight (kg)	5.37	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-305
Light Output		Inrush Current Peak (A)	60
Lumens (lm)	17000	Surge Protection (kV)	1
Efficacy (lm/W)	85	Conductor Size (mm)	1.5
LED		Terminal Type	3 pole screw down
CCT (K)	3000		
CRI	65		
Macadam Elipses	4		

Order Code: XCSF200WW
200W - High Output Slim Floodlight - IP65 - 3000K - Black

Dimensions

A (mm)	485
B (mm)	325
C (mm)	110

Line Drawing

