

**Order Code: XCSF20NW**

20W - High Output Slim Floodlight - IP65 - 4000K - Black



**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 80 lumens per watt efficacy

**Construction**

- White or black body finish
- Breather gland for reducing condensation



**Technical Data**

General		Electrical	
Luminaire Wattage (W)	20	Rated Input Current (A)	0.095
Weight (kg)	0.93	Power Factor (pf)	0.9
Operating Temperature (ta °C)	-20 to 25	Input Voltage Range (VAC)	100-240
<b>Light Output</b>		Inrush Current Peak (A)	60
		Surge Protection (kV)	0.5
		Conductor Size (mm)	1.5
Lumens (lm)	1600	Terminal Type	3 pole screw down
Efficacy (lm/W)	80		
<b>LED</b>			
CCT (K)	4000		
CRI	65		
Macadam Ellipses	4		

**Order Code:** XCSF20NW

20W - High Output Slim Floodlight - IP65 - 4000K - Black

### Dimensions

A (mm)	200
B (mm)	150
C (mm)	50

### Line Drawing

