# xcite LED Lighting
## Data Sheet

**Order Code:** XCSF30NW

30W - High Output Slim Floodlight - IP65 - 4000K - Black



### Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 90 lumens per watt efficacy

### Construction

- White or black body finish
- Breather gland for reducing condensation

## Technical Data

### General

| | |
|---|---|
| Luminaire Wattage (W) | 30 |
| Weight (kg) | 1.61 |
| Operating Temperature (ta °C) | -20 to 25 |

### Light Output

| | |
|---|---|
| Lumens (lm) | 2700 |
| Efficacy (lm/W) | 90 |

### LED

| | |
|---|---|
| CCT (K) | 4000 |
| CRI | 65 |
| Macadam Elipses | 4 |

### Electrical

| | |
|---|---|
| Rated Input Current (A) | 0.13 |
| Power Factor (pf) | 0.9 |
| Input Voltage Range (VAC) | 100-240 |
| Inrush Current Peak (A) | 90 |
| Surge Protection (kV) | 1 |
| Conductor Size (mm) | 1.5 |
| Terminal Type | 3 pole screw down |

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk

# xcite LED Lighting

## Data Sheet

**Order Code:** XCSF30NW

30W - High Output Slim Floodlight - IP65 - 4000K - Black

### Dimensions

| | |
|---|---|
| Length (mm) | 305 |
| Width (mm) | 190 |
| Depth (mm) | 64 |

### Line Drawing

Image not found or type unknown

Technical
Stafford Park 12
Telford, Shropshire,
TF3 3BJ

T: +44 (0)1952 292441
E: sales@xciteledlighting.co.uk
W: www.xciteledlighting.co.uk