

Order Code: XCSF50NWP

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - Black

**Features**

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
- Available with Photocell [50W & 80W outputs]
- Available with PIR [Up to 50W]
- Available in 6 sizes
- Available in 8 different outputs
- High quality toughened safety glass
- Supplied with stirrup and 1m of flex for column, bracket or surface fix
- Weatherproof IP65 construction
- Up to 94 lumens per watt efficacy

Construction

- White or black body finish
- Breather gland for reducing condensation

**Technical Data****General**

Luminaire Wattage (W)	50
Weight (kg)	2.56
Operating Temperature (ta °C)	-20 to 25

Light Output

Lumens (lm)	4700
Efficacy (lm/W)	94

LED

CCT (K)	4000
CRI	65
Macadam Ellipses	4

Electrical

Rated Input Current (A)	0.2
Power Factor (pf)	0.9
Input Voltage Range (VAC)	100-240
Inrush Current Peak (A)	90
Surge Protection (kV)	1
Conductor Size (mm)	1.5
Terminal Type	3 pole screw down

Order Code: XCSF50NWP

50W - High Output Slim Floodlight - IP65 - PIR - 4000K - Black

Dimensions

A (mm)	360
B (mm)	235
C (mm)	70

Line Drawing

