

Order Code: XCSF50WW
50W - High Output Slim Floodlight - IP65 - 3000K - Black



Features

- Ideal for retrofit of existing halogen fixtures, lighting buildings, car parks or doorways
• Available with Photocell [50W & 80W outputs]
• Available with PIR [Up to 50W]
• Available in 6 sizes
• Available in 8 different outputs
• High quality toughened safety glass
• Supplied with stirrup and 1m of flex for column, bracket or surface fix
• Weatherproof IP65 construction
• Up to 82 lumens per watt efficacy

Construction

- White or black body finish
• Breather gland for reducing condensation



Technical Data

Table with 2 main sections: General and Electrical. General includes Luminaire Wattage (W), Weight (kg), Operating Temperature (ta °C), Light Output (Lumens (lm), Efficacy (lm/W)), and LED (CCT (K), CRI, Macadam Elipses). Electrical includes Rated Input Current (A), Power Factor (pf), Input Voltage Range (VAC), Inrush Current Peak (A), Surge Protection (kV), Conductor Size (mm), and Terminal Type.

Order Code: XCSF50WW
50W - High Output Slim Floodlight - IP65 - 3000K - Black

Dimensions

A (mm)	355
B (mm)	235
C (mm)	70

Line Drawing

