

Order Code: XCSL433NWMS

33W - Surface module - Fixed output - Microwave sensor - 4000K



Features

- Suitable for schools, corridors and general areas
- Available in 2 lengths and 2 outputs
- Surface mounted

Construction

- Steel body in white finish
- Opal polycarbonate diffuser
- Rear BESA fixings or side cable entry
- Supplied as standard with neutral white [4000K] LED



Technical Data

General

| | |
|-------------------------------|---------|
| Luminaire Wattage (W) | 33 |
| Weight (kg) | 1.70 |
| Operating Temperature (ta °C) | 0 to 25 |

Light Output

| | |
|-----------------|------|
| Lumens (lm) | 3900 |
| Efficacy (lm/W) | 118 |

LED

| | |
|------------------|------|
| CCT (K) | 4000 |
| CRI | 80 |
| Macadam Ellipses | <3 |

Driver

| | |
|---------------------|-----|
| Driver Current (mA) | 700 |
| Forward Voltage (V) | 41 |

Electrical

| | |
|---------------------------|------------------|
| Rated Input Current (A) | 0.15 |
| Power Factor (pf) | 0.95 |
| Input Voltage Range (VAC) | 220 to 240 |
| Inrush Current Peak (A) | 80 |
| Surge Protection (kV) | 2 |
| Conductor Size (mm) | 0.5 to 2.5 |
| Terminal Type | 4-POLE GRIP-WIRE |

Order Code: XCSL433NWMS

33W - Surface module - Fixed output - Microwave sensor - 4000K

Dimensions

| | |
|--------|------|
| A (mm) | 1203 |
| B (mm) | 154 |
| C (mm) | 70 |

Line Drawing

