

Order Code: XCSL4X1M3

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Emergency



Features

- Suitable for schools, offices, corridors and general areas
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [23W/29W/35W/40W]
- Up to 113 lumens per watt efficacy
- Surface mounted

Construction

- Low glare prismatic, polycarbonate, Tp(a) rated diffuser
- Steel body in white finish
- Rear BESA fixings or side cable entry



Technical Data

General

Luminaire Wattage (W)	23W/29W/35W/40W
Weight (kg)	2.64
Operating Temperature (ta °C)	5° to 25°

Light Output

Lumens (lm)	2600/3300/3900/4500
Efficacy (lm/W)	113

LED

CCT (K)	3000K/4000K/6000K
CRI	83 to 87
Macadam Elipses	3.1 to 10.1

Driver

Driver Current (mA)	200 to 350
Forward Voltage (V)	103 to 108

Emergency

Emergency Lumen Operating	283
Emergency Wattage (W)	3

Electrical

Rated Input Current (A)	0.11 to 0.18
Power Factor (pf)	0.9 to 0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	18.3
Surge Protection (kV)	L-N 1KV, LN-PG 2KV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

Order Code: XCSL4X1M3

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Emergency

Dimensions

A (mm)	1225
B (mm)	155
C (mm)	55

Line Drawing

