

### Order Code: XCSL4X1M3MS

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Emergency - Microwave sensor



#### Features

- Suitable for schools, offices, corridors and general areas
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [23W/29W/35W/40W]
- Up to 113 lumens per watt efficacy
- Surface mounted

#### Construction

- Low glare prismatic, polycarbonate, Tp(a) rated diffuser
- Steel body in white finish
- Rear BESA fixings or side cable entry



#### Technical Data

##### General

Luminaire Wattage (W)	23W/29W/35W/40W
Weight (kg)	2.74
Operating Temperature (ta °C)	5° to 25°

##### Light Output

Lumens (lm)	2600/3300/3900/4500
Efficacy (lm/W)	113

##### LED

CCT (K)	3000K/4000K/6000K
CRI	83 to 87
Macadam Ellipses	3.1 to 10.1

##### Driver

Driver Current (mA)	200 to 350
Forward Voltage (V)	103 to 108

##### Emergency

Emergency Lumen Operating	283
Emergency Wattage (W)	3

##### Electrical

Rated Input Current (A)	0.11 to 0.18
Power Factor (pf)	0.9 to 0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	18.3
Surge Protection (kV)	L-N 1KV, LN-PG 2KV
Conductor Size (mm)	0.5 to 2.5
Terminal Type	4 pole piano key

### Order Code: XCSL4X1M3MS

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Emergency - Microwave sensor

#### Dimensions

A (mm)	1225
B (mm)	155
C (mm)	55

#### Line Drawing

