

Order Code: XCSL4X1MS

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Microwave sensor



Features

- Suitable for schools, offices, corridors and general areas
- CCT selectable via selector switch [3000K/4000K/6000K]
- Wattage selectable via selector switch [23W/29W/35W/40W]
- Up to 113 lumens per watt efficacy
- Surface mounted

Construction

- Low glare prismatic, polycarbonate, Tp(a) rated diffuser
- Steel body in white finish
- Rear BESA fixings or side cable entry



Technical Data

General		Electrical	
Luminaire Wattage (W)	23W/29W/35W/40W	Rated Input Current (A)	0.11 to 0.18
Weight (kg)	2.24	Power Factor (pf)	0.9 to 0.96
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	18.3
		Surge Protection (kV)	L-N 1KV, LN-PG 2KV
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	3 pole piano key
Light Output			
Lumens (lm)	2600/3300/3900/4500		
Efficacy (lm/W)	113		
LED			
CCT (K)	3000K/4000K/6000K		
CRI	83 to 87		
Macadam Elipses	3.1 to 10.1		
Driver			
Driver Current (mA)	200 to 350		
Forward Voltage (V)	103 to 108		

Order Code: XCSL4X1MS

Surface Linear X1 - 1200mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser - Microwave sensor

Dimensions

A (mm)	1225
B (mm)	155
C (mm)	55

Line Drawing

