

**Order Code: XCSL553NWM3**

53W - Surface module - Fixed output - Emergency - 4000K



**Features**

- Suitable for schools, corridors and general areas
- Available in 2 lengths and 2 outputs
- Surface mounted

**Construction**

- Steel body in white finish
- Opal polycarbonate diffuser
- Rear BESA fixings or side cable entry
- Supplied as standard with neutral white [4000K] LED



**Technical Data**

**General**

Luminaire Wattage (W)	53
Weight (kg)	2.40
Operating Temperature (ta °C)	5 to 25

**Light Output**

Lumens (lm)	6200
Efficacy (lm/W)	117

**LED**

CCT (K)	4000
CRI	80
Macadam Elipses	<3

**Driver**

Driver Current (mA)	1050
Forward Voltage (V)	46.5

**Emergency**

Emergency Lumen Operating	320
---------------------------	-----

**Electrical**

Rated Input Current (A)	0.24
Power Factor (pf)	0.96
Input Voltage Range (VAC)	220 to 240
Inrush Current Peak (A)	50
Surge Protection (kV)	2
Conductor Size (mm)	0.5 to 2.5
Terminal Type	3-POLE GRIP-WIRE

**Order Code:** XCSL553NWM3

53W - Surface module - Fixed output - Emergency - 4000K

### Dimensions

A (mm)	1503
B (mm)	154
C (mm)	70

### Line Drawing

