


Order Code: XCSL5X1

Surface Linear X1 - 1500mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser



Features

- Suitable for schools, offices, corridors and general areas
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Wattage adjustable via selector switch [28W/34W/41W/47W]
- Up to 119 lumens per watt efficacy
- Surface mounted

Construction

- Low glare prismatic, polycarbonate, Tp(a) rated diffuser
- Steel body in white finish
- Rear BESA fixings or side cable entry



Technical Data

General		Electrical	
Luminaire Wattage (W)	28W/34W/41W/47W	Rated Input Current (A)	0.13 to 0.21
Weight (kg)	2.68	Power Factor (pf)	0.92 to 0.96
Operating Temperature (ta °C)	0° to 25°	Input Voltage Range (VAC)	220 to 240
		Inrush Current Peak (A)	43.6
Light Output		Surge Protection (kV)	L-N 1KV, LN-PG 2KV
Lumens (lm)	3300/4100/4900/5600	Conductor Size (mm)	0.5 to 2.5
Efficacy (lm/W)	119	Terminal Type	3 pole piano key
LED			
CCT (K)	3000K/4000K/6000K		
CRI	83 to 87		
Macadam Elipses	2.8 to 8.8		
Driver			
Driver Current (mA)	200 to 350		
Forward Voltage (V)	127 to 133		

Order Code: XCSL5X1

Surface Linear X1 - 1500mm - 3000K-6000K + Wattage Switchable - Prismatic diffuser

Dimensions

A (mm)	1525
B (mm)	155
C (mm)	55

Line Drawing

