

Order Code: XCSR5M2465NW  
XCITE IP65 24V 5M LED Strip Reel - 4000K



Features

- Suitable for kitchens, bars, restaurants and under counter displays
- 3M adhesive backing tape
- Supplied with 1M pre-wired driver connector lead
- 1000 lumens per metre

Construction

- Available in warm white [3000K], neutral white [4000K] or daylight [6000K]
- 120 LEDs per metre
- Cuttable every 50mm
- 9.6W per metre

Technical Data

| General                       |            | Electrical          |            |
|-------------------------------|------------|---------------------|------------|
| Weight (kg)                   | 0.15       | Conductor Size (mm) | AWG22      |
| Operating Temperature (ta °C) | 0 to 25    | Terminal Type       | Solder Pad |
| Light Output                  |            |                     |            |
| Efficacy (lm/W)               | 100        |                     |            |
| LED                           |            |                     |            |
| CCT (K)                       | 4000       |                     |            |
| CRI                           | 80         |                     |            |
| Macadam Ellipses              | 0.9 F 4000 |                     |            |
| Driver                        |            |                     |            |
| Forward Voltage (V)           | 24         |                     |            |

Order Code: XCSR5M2465NW  
XCITE IP65 24V 5M LED Strip Reel - 4000K

Dimensions

|        |      |
|--------|------|
| A (mm) | 5000 |
| B (mm) | 8    |
| C (mm) | 3    |

Line Drawing

