

Order Code: XCTLD6CT

Xcite TRIMLESS FRD 6W recessed fire rated downlight - 3000-6000K

Features

- Ultra-low profile design perfect for installations in shallow ceiling voids, offering more flexibility in compact spaces.
- CCT adjustable via 3-way selector switch [3000K/4000K/6000K]
- Dimmable as standard
- 60° Beam Angle
- 30 minute fire rating with Staircraft I-Joist and METAL WEB Joist [[Compatibility Matrix](#)]

Construction

- Steel body providing a high level of fire protection in accordance with Building Regulations Part B
- Loop in/out mains connections with easy-fit connector
- CRI: Ra>80



Technical Data

| General | | Electrical | |
|-------------------------------|-------------------|---------------------------|------------------|
| Luminaire Wattage (W) | 6 | Rated Input Current (A) | 0.031 |
| Weight (kg) | 0.20 | Power Factor (pf) | 0.8 |
| Operating Temperature (ta °C) | 0 to 25 | Input Voltage Range (VAC) | 220-240 |
| | | Surge Protection (kV) | 0.5 |
| Light Output | | Conductor Size (mm) | 0.5 - 2.5 |
| Lumens (lm) | 650 | Terminal Type | 3-Pole Grip-wire |
| Efficacy (lm/W) | 108 | | |
| LED | | | |
| CCT (K) | 3000K/4000K/6000K | | |
| CRI | 80 | | |
| Macadam Elipses | 6 | | |

Order Code: XCTLD6CT

Xcite TRIMLESS FRD 6W recessed fire rated downlight - 3000-6000K

Dimensions

| | |
|--------------|-------|
| C (mm) | 70 |
| ----- | ----- |
| Cut Out (mm) | 95 |
| ----- | ----- |
| Dia. (mm) | 145 |
| ----- | ----- |

