xcite LED Lighting

Data Sheet



Order Code: XCUCL3NW

3W - Slimline Under Cupboard Cabinet Light - IP20 - 4000K



Features

- Ideal for replacement of linear fluorescent fixtures
- Available in 5 lengths
- · Full set of connectors and accessories supplied
- Slimline profile for discreet installation
- Up to 100 lumens per watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array











Technical Data

	General			Ele
Luminaire Wattage (W)		3	Rated Input Current (A)	
Weight (kg)		0.08	Power Factor (pf)	
	Light Output		Input Voltage Range (VAC)	
Lumens (Im)	Light Output	300	Inrush Current Peak (A)	
Efficacy (Im/W)		100	Surge Protection (kV)	
			Conductor Size (mm)	
	LED		Terminal Type	
CCT (K)		4000		
CRI		80		
Macadam Elipses		4		

Electrical			
Rated Input Current (A)	0.01		
Power Factor (pf)	0.4		
Input Voltage Range (VAC)	200-240		
Inrush Current Peak (A)	9		
Surge Protection (kV)	0.5		
Conductor Size (mm)	0.75		
Terminal Type	Bare wire		

xcite LED Lighting

Data Sheet



Order Code: XCUCL3NW

3W - Slimline Under Cupboard Cabinet Light - IP20 - 4000K

Dimensions

A (mm)	222
B (mm)	23
C (mm)	37

Line Drawing

