

Order Code: XCUCL5CT

CABINET LIGHT CC Cabinet/Shaver Lights 5W - 3000K-4000K



Features

- Slimline profile for discreet installation
- CCT adjustable via 2-way selector switch [3000K/4000K]
- Up to 100 lumens per watt efficacy

Construction

- Extruded plastic body
- LED SMD modules array



Technical Data

General		Electrical	
Luminaire Wattage (W)	5	Rated Input Current (A)	0.03
Weight (kg)	0.10	Power Factor (pf)	0.75
Operating Temperature (ta °C)	0 to 25	Input Voltage Range (VAC)	220-240
		Inrush Current Peak (A)	5
		Surge Protection (kV)	0.5
		Conductor Size (mm)	0.5 to 2.5
		Terminal Type	2 core flex
Light Output			
Lumens (lm)	500		
Efficacy (lm/W)	100		
LED			
CCT (K)	3000K/4000K		
CRI	80		
Macadam Ellipses	5		
Driver			
Driver Current (mA)	140		
Forward Voltage (V)	30		

Order Code: XCUCL5CT

CABINET LIGHT CC Cabinet/Shaver Lights 5W - 3000K-4000K

Dimensions

A (mm)	296
B (mm)	23
C (mm)	37

Line Drawing

