

### Order Code: XCWL23NWPCM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K



#### Features

- Ideal for retrofit of HID discharge wallpacks
- Suitable for exterior walls and entrance areas
- Sensor options available
- Photocell option available
- Up to 70 lumens per watt efficacy

#### Construction

- Polycarbonate body and diffuser
- Integral emergency option available
- Supplied as standard with neutral white [4000K] LED



#### Technical Data

General		Electrical	
Luminaire Wattage (W)	23	Rated Input Current (A)	0.12
Weight (kg)	1.50	Power Factor (pf)	0.9
Operating Temperature (ta °C)	5 to 25	Input Voltage Range (VAC)	220-240
Light Output		Surge Protection (kV)	1
		Conductor Size (mm)	2.5
		Terminal Type	3 pole piano key
LED			
CCT (K)	4000		
CRI	80		
Macadam Elipses	4		
Emergency			
Emergency Lumen Operating	130		
Emergency Wattage (W)	2		

### Order Code: XCWL23NWPCM3

23W - Bulkhead High Output Wall Pack - IP65 - 4000K - Photocell - 3hrs Maintained Emergency - 4000K

#### Dimensions

A (mm)	307
B (mm)	257
C (mm)	105

#### Line Drawing

